

Bitumen sealant

For sealing joints between bitumen strips

Excellent adhesion to bitumen strips

Very secure sealing of roof sheeting and roofing cardboard

Good adhesion to damp substrates

- Use largely unaffected by the weather
- Suitable for emergency repairs

Ageing and weather-resistant

Suitable for elastic moulding

Contents	310 ml
Container	Cartridge
Chemical basis	Bitumen
Colour	Black
Continuous motion absorption	10 %
Min. skin-formation time	30 min
Conditions for skin-formation time	at 23 °C and 50% relative humidity
Min. processing temperature	1 °C
Max. processing temperature	30 °C



Art. No. 0890 103

P. Qty.: 1 / 12

Details/Application

For the filling of bitumen strips and their connections.

For filling roof passages, e.g. domed roof lights, ventilation ducts, antennas or chimneys, as well as edge connections. Typical substrates without primer: bitumen, zinc plating, copper plating, stainless steel, concrete, clinker.

Instructions

Use primer on highly porous substrates.

Please observe the „General Notes on Application for Sealants“ and „Construction Material Compatibility of Würth Sealants“ overview sheet.

Notice

Repairs performed in damp conditions must be checked when dry

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.

Related products	Art. No.
Cartridge cutter	0715 66 09
Manual cartridge gun Standard	0891 000 001
Primer Butyl primer 750 ml	0892 875