



DECLARATION OF PERFORMANCE

CE_DoP_Rf-t_C1_EN ■ G-05/2018

1. Unique identification code of the product-type:	CR2
2. Intended use/es:	Circular fire damper to be used in conjunction with partitions to maintain fire compartments in heating, ventilating and air conditioning installations.
3. Manufacturer:	Rf-Technologies NV, Lange Ambachtstraat 40, B-9860 Oosterzele
4. System/s of AVCP:	System 1
5. Harmonised standard / European Assessment Document; notified body / European Technical Assessment, Technical Assessment Body, notified body; certificate of constancy of performance:	EN 15650:2010, BCCA with identification number 0749; BCCA-0749-CPR-BC1-606-0464-15650.01-2517
6. Declared performance according to EN 15650:2010	(Fire resistance according to EN 1366-2 and classifications according to EN 13501-3)

Essential characteristics					Performance	
Range	Wall type	Wall	Sealing	Installation	Classification	
Ø 200-630 mm	Rigid wall	Aerated concrete ≥ 100 mm	Mortar / Gypsum	1	El 120 (v _e i ↔ o) S - (500 Pa)	
			Stone wool + coating ≥ 140 kg/m ³	1	El 90 (v _e i ↔ o) S - (300 Pa)	
	Rigid floor	Aerated concrete ≥ 150 mm	Mortar	2	El 120 (h _o i ↔ o) S - (500 Pa)	
			Stone wool + coating ≥ 140 kg/m ³	2	El 120 (h _o i ↔ o) S - (300 Pa)	
	Flexible wall	Metal studs gypsum plasterboard Type A (EN 520) ≥ 100 mm	Stone wool ≥ 40 kg/m ³ + cover plates	1	El 60 (v _e i ↔ o) S - (500 Pa)	
			Gypsum	1	El 60 (v _e i ↔ o) S - (500 Pa)	
			Stone wool + coating ≥ 140 kg/m ³	1	El 60 (v _e i ↔ o) S - (300 Pa)	
		Metal studs gypsum plasterboard Type F (EN 520) ≥ 100 mm	Stone wool ≥ 40 kg/m ³ + cover plates	1	El 90 (v _e i ↔ o) S - (300 Pa)	
			Gypsum	1	El 120 (v _e i ↔ o) S - (500 Pa)	
			Stone wool + coating ≥ 140 kg/m ³	1	El 90 (v _e i ↔ o) S - (300 Pa)	
		Gypsum blocks ≥ 70 mm	Block glue	1	El 120 (v _e i ↔ o) S - (500 Pa)	
1	Type of installation: built-in, 0-360°. Minimal distances authorised with axis till 45°.					
2	Type of installation: built-in, 0-360°. Minimal distances authorised.					

Hammonised standard
EN 15650:2010

Essential characteristics	Performance
Nominal activation conditions/sensitivity:	Pass
Response delay (response time): closure time	Pass
Operational reliability: cycling	CFTH - 50 cycles; MANO - 300 cycles; B(L)F(T) - 10000 cycles; BFL(T) - 10000 cycles; BFN(T) - 10000 cycles; ONE - 10000 cycles; UNIQ - 10000 cycles
Durability of response delay:	Pass
Durability of operational reliability:	Pass
Protection against corrosion according to EN 60068-2-52:	Pass
Damper casing leakage according to EN 1751:	≥ class B

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Frank Verlinden, Product Manager

Frank Verlinden
Oosterzele, 05/2018



Hammonised standard
EN 15650:2010