

## Sound data and power consumption HRC-400 EcoMax and MaxComfort

Capacity Qv - m <sup>3</sup> /h	Print Δ P st- Pa	Absorbed power W el	SFP Wh/ m <sup>3</sup>	Lw housing dB(A)	Lw return dB(A)	Lw supply dB(A)
400	150	117	0,29	56	49	69
400	100	103	0,26	56	50	73
350	150	94	0,27	54	49	66
350	100	82	0,23	52	48	64
350	50	68	0,19	52	44	63
300	150	72	0,24	51	47	63
300	100	62	0,21	50	42	61
280	50	47	0,17	47	45	56
250	100	47	0,19	46	41	62
250	50	37	0,15	43	43	58
200	50	28	0,14	42	43	54
150	25	17	0,12	38	43	48
100	25	12	0,12	36	37	42

\* Cabin radiation measured according to ISO 3741:2010

\* SFP in Wh/m<sup>3</sup> calculated with measured data according to 13141-7:2018

\* Return noise measured according to ISO 5135:197 (measured values include end-of-reflection correction)

\* Supply noise measured according to IOS 5135:1997 (measured values include end-of-reflection correction)

\* Connection diameter used 180mm

**-> [Click here](#) and see the Orcon HRC 400 EcoMax online with all specifications and documentation**